

Sanitary pressure gauge - Male connection (3-A marking)

Model: P753S series

Spec. sheet no. PD07-06



Service intended

P753S series have diaphragm seal to be combined with a pressure gauge. These series are suitable to be used for the situation where corrosive, contaminated, hot, and viscous pressure mediums are present, and it could be used for a chemical, food, beverage, biochemical, and pharmaceutical industry.

Special features

3-A certificated
Suitable for SIP and CIP
All stainless steel and welded construction

Nominal diameter

63 and 100 mm

Accuracy

$\pm 1.6\%$ of full scale
If scale range less than 100 psi : $\pm 2.0\%$ of full scale

Scale range

0 ~ 3.5 MPa, single

Working pressure

Steady pressure : 75 % of full scale value
Fluctuating pressure : 67 % of full scale value

Operating temperature

Ambient : -20 ~ 65 °C
Fluid : Max. 121 °C

Temperature effect

Accuracy at temperature above and below the reference temperature (20 °C) will be effected by approximately $\pm 0.5\%$ per 10 °C of full scale



Standard features

Process connection

DIN Round thread 28-8

Pointer

Black painted aluminium alloy

Case and cover

Stainless steel (304SS)
Electropolished with pressure relief

Helium leak rate

Tested to confirm leakage rates of less than 10^{-8} mbar • l /sec

Window

Safety glass

System filling

Food grade oil (FDA certified)

Movement

Stainless steel

O-ring

Supplied by FDA approved Supplier (Viton)

Dial

White aluminium, with pointer stop pin
With black/red lettering, dual pressure scale

Option

Material of wetted parts : Electropolished 316L SS

WISE

Main order

Ordering information

1. Base model

P753S Sanitary pressure gauge - Male connection (3-A marking)

2. Nominal diameter and mounting type

7A 63 mm, bottom connection (refer to code A)

8A 100 mm, bottom connection (refer to code A)

3. Body and process connection material

D 316SS

4. Process connection

F DIN Round thread 28-8

5. Unit

H bar

I MPa

J kPa

6. Range

XXX Refer to pressure range table

7. Diaphragm material

E 316L SS

8. Option

0 None

1 Accessories

Sample ordering code



1	2	3	4	5	6	7	8
P753S	8A	D	F	H	XXX	E	0



© WISE Control Inc. All rights reserved. ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

P753S : Type of mounting

Code A



Dimensions (mm)

Dial size	Available code	A	B	D ± 2	E ± 2	F ± 1
63	A	64	62	34	79.7	11
100	A	101.3	99	50	105.5	16

Range table

Range and code	Unit and code		Pressure connection ¾"
	H : bar	I : MPa	
042	0 ~ 2	0 ~ 0.2	O
044	0 ~ 4	0 ~ 0.4	O
045	0 ~ 6	0 ~ 0.6	O
047	0 ~ 10	0 ~ 1	O
050	0 ~ 15	0 ~ 1.5	O
051	0 ~ 20	0 ~ 2	O
052	0 ~ 25	0 ~ 2.5	O
054	0 ~ 35	0 ~ 3.5	O

O : Available